

i-Nova3-Zoom

8.9 MP Camera with 3 motorized zoom lens



Accident prevention



Surveillance



Access control

- 8.9 MP Camera with 3 motorized zoom lens
- Te2v EV2S8M9C CMOS global shutter sensor
- 10 ~ 300 mm (X30) zoom lens
- 3 motorized IR corrected zoom lens
- GenICam, ONVIF



Specification

Model	iN3Z-89EC-10Z300
Image sensor	Te2v Emerald EV2S8M9C, 2/3", CMOS
Resolution / Frame rate	4096 x 2160 pixels / 30 fps
Shutter mode	Global shutter
Lens control	Motorized zoom / focus / iris
Focal length	10 ~ 300 mm
Filter switcher	IR cut / anti-fog / off
Trigger mode	Pseudo trigger, external trigger (One shot / multi shot), software trigger
Protocol	RTSP (H.264 / H.265, MJPEG*), GigE Vision protocol, GenICam, ONVIF**
I/O port	1 x Input for triggering (Low voltage : 0V ~ 0.8 V / high level : 2 V ~ 24 V) 2 x Strobe (TTL, open collector) RS232C
Interface	100 / 1000 Mbps Ethernet (RJ45)
Operating temperature / Humidity	0 °C ~ 50 °C / 20 % ~ 80 %
HDMI	HDMI A (Locking) ※ UHD support not available
Power supply / Power consumption	12 V DC ~ 24 V DC / Max.14 W
Dimension / Weight	90 x 90 x 204 mm / 2,000 g
SDK / Certificate	Viewer and example code (C++) / KC, CE

*UHD support unavailable in MJPEG
**Camera settings control unavailable

Dimension

*mm

