

i-Nova4-Motor

5 MP Camera with 3 motorized zoom lens



Accident prevention



Surveillance



Speed enforcement



- 5 MP, 30 fps @ 2560 x 1936 pixels
- Te2v EV2S05MC CMOS global shutter sensor
- 10 ~ 50 mm (X5) zoom lens
- 3 motorized IR corrected zoom lens
- GenICam, ONVIF

Specification

Model	iN4M-50EC-10M50
Image sensor	Te2v Emerald EV2S05MC, 1/1.8", CMOS
Resolution / Frame rate	2560 x 1936 pixels / 30 fps
Shutter mode	Global shutter
Lens control	Motorized zoom / focus / iris
Focal length	10 ~ 50 mm
Filter switcher	IR cut filter on / off
Trigger mode	Pseudo trigger, external trigger (One shot / multi shot), software trigger
Protocol	RTSP (H.264 / H.265, MJPEG), GigE Vision protocol, GenICam, ONVIF
I/O port	1 x Input for triggering (Low voltage : 0V ~ 0.8V / high level : 2V ~ 24V) 2 x Strobe (TTL, open collector) RS232C, RS485
Interface	100 / 1000 Mbps Ethernet (RJ45)
Power supply / Power consumption	5W
Operating temperature / Humidity	0 °C ~ 50 °C / 20 % ~ 80 %
Dimension / Weight	70X72X108mm / 574g
SDK	Viewer and example code (C++)
Certificate	KC, CE

Dimension

*mm

